

Compuprint PAGERMASTER 120e

The fast, compact laser printer for personal and small office use



Designed for speed, quality and productivity

The PageMaster 120e is a compact printer that will turn out up to 12 pages per minute at a resolution of up to 1200x1200 dpi. Its innovative controller has a 66 MHz, RISC processor unequalled on the market for power, and offers a competitive cost/performance ratio. PLC6 emulation and optional Adobe PostScript Level 3 ensure maximum quality reproduction of text, graphics and images. Standard memory is 4 MB, expandable to 68MB.

Versatile and dependable

The PageMaster 120e meets any printing requirement thanks to its capacious 250-sheet universal input tray and automatic feeder holding up to 100 sheets or 10 envelopes. The output bin holds 250 sheets (face down) and there is also a rear output stacker holding 100 sheets (face up). A second 550-sheet input tray is available as an optional extra. The printer is connected to the computer by parallel and USB interfaces, and with the optional Ethernet 10/100baseT card installed it can be connected to a network.

The PageMaster 120e is a laser printer capable of 12 ppm, ideal for the most demanding of professional requirements and for small workgroups. It is simple to install and easy to use. Its key attributes are versatility and compactness, and it offers unparalleled print speed and quality. It is easily integrated into a network, as it supports the most widely used software environments, namely Windows 95/98/2000, NT, Apple Macintosh, guaranteeing the compatibility of applications through PCL and PostScript.



Compuprint

Compuprint PAGEMASTER 120e

The fast, compact laser printer for personal and small office use

Technical specifications

| | |
|-------------------------------|---|
| Printing technology: | Monochrome laser electrophotographic. |
| Speed: | 12 pages per minute (ppm) |
| Print resolution: | 600x600 dots per inch (dpi), 1200x1200 dpi in enhanced mode |
| Microprocessor: | RISC 32-bit, 66 MHz |
| Emulations: | PCL6, Adobe PostScript Lev 3 (optional) with automatic emulation switching (AES) |
| Memory: | 4 MB std (68 MB max) |
| Interfaces: | Parallel bidirectional IEEE 1284, USB with automatic interface switching (AIS) Optional interfaces: Ethernet 10/100 |
| Font: | 45 Type 1 PCL |
| Workload: | 20,000 pages per month |
| Paper handling: | A5-A4 / 60 - 163 g/m2 Standard Feed: Universal input tray holding 250 x A4 sheet Multi-bypass feeder 100 sheets / 10 envelopes Output bin holding 500 sheets (face down) Rear stacker holding 100 sheets (face up) Optional: Input tray holding 550 x A4 sheet |
| Dimensions and weight: | 360mm x 407mm x 249mm (LxDxH) / 11 kg |
| Consumables: | Toner cartridge: 6,000 pages (all-in-one) @ 5% coverage |
| Power Supply and Consumption: | 220/240V 50/60 Hz 300 W max Energy Star |
| Ambient Conditions: | Temperature: 10 °C to 30 °C (operation and storage) Relative humidity: 15-85% without condensation Acoustic emissions: 47 dBA printing / 35 dBA on standby |
| Conformity with standards: | CE, GOST, GS |
| Driver, Software, Networking: | Operating Systems: Windows 95,98,2000, NT 4.0, MacIntosh |



Compuprint SpA
Via Martiri d'Italia, 26
10014 Caluso (TO) Italy
Tel. +39 011 98 92 111
Fax +39 011 98 92 748
www.compuprint.net