

## 9000 *plus* – 10000 *plus* Series

The **fastest** Serial Printer Line available on the market today that offers the highest level of performance for their respective speeds.



9050 *plus* - 9065 *plus* - 9080 *plus* - 9300 *plus*



10300 *plus*

**9000 *plus* – 10000 *plus* Series** are now fully equipped as standard with standard Parallel , Serial, USB 2.0 and LAN Interfaces and adopts new and improved electronic and mechanical solutions that moves their print performance to an unbeatable level



### INDUSTRIAL DESIGN

- Heavy duty industrial design for the harshest of print environments.
- Durable, all metal covers on the 10300 Plus.



### REMOTE MANAGEMENT

- Real-time status updates, remote configuration of multiple printers, and access to a fully functional virtual operator panel.



### HIGH PERFORMANCE

- Unmatched print speeds of up to 1,300 cps and 860 pages/hour.
- Optimal performance for up to 75,000 pages per month workload.
- 18 and 24 pins print-head technologies up to 800 Million Characters life



### EASY TO USE

- Customizable intelligent forms handling for up to 8 templates.
- Optional second tractor for two application support.

# SPECIFICATIONS

## PRINT TECHNOLOGY

9050-9065-9080-10300	24-Pin serial dot matrix printer - 136 columns @10cpi
9300-9300lpds	18-Pin serial dot matrix printer 136 columns @10cpi

## THROUGHPUT (ISO/IEC 10561 - @10CPI)

	DIN Letter	Spreadsheet
9050	Up to 500 PPH	Up to 316 PPH
9065	Up to 610 PPH	Up to 380 PPH
9080	Up to 660 PPH	Up to 450 PPH
9300-9300lpds	Up to 860 PPH	Up to 590 PPH
10300	Up to 860 PPH	Up to 560 PPH

## THROUGHPUT (Draft Mode - @10CPI)

Chars per Line	40	80	136
9050	340 LPM	240 LPM	175 LPM
9065	410 LPM	290 LPM	210 LPM
9080	450 LPM	330 LPM	250 LPM
9300-9300lpds	620 LPM	460 LPM	325 LPM
10300	610 LPM	460 LPM	320 LPM

## PRINT SPEED (CPS) @ 10 CPI, 12 CPI, 15 CPI

9050	<b>HSD:</b> 720 <b>Draft:</b> 600, 720, 800 <b>Best Draft:</b> 330, 400, 500 <b>NLQ:</b> 220, 260, 330 <b>LQ:</b> 110, 133, 166
9065	<b>HSD:</b> 720 <b>Draft:</b> 650, 780, 900 <b>Best Draft:</b> 400, 480, 600 <b>NLQ:</b> 267, 320, 400 <b>LQ:</b> 133, 166, 200
9080	<b>HSD:</b> 900 <b>Draft:</b> 800, 960, 1200 <b>Best Draft:</b> 400, 480, 600 <b>NLQ:</b> 267, 320, 400 <b>LQ:</b> 133, 166, 200
9300-9300lpds	<b>HSD:</b> 1300 <b>Draft:</b> 950, 1100, 1100 <b>Best Draft:</b> 480, 480, 480 <b>LQ:</b> 133, 166, 200
10300	<b>HSD:</b> 1300 <b>Draft:</b> 950, 1100, 1400 <b>Best Draft:</b> 500, 600, 600 <b>NLQ:</b> 330, 360, 450 <b>LQ:</b> 160, 180, 225

## MEDIA SPECIFICATIONS

Media Type	Continuous Form, front loading
Width	76 to 432 mm (3 to 17 inches)
Length	78 to 610 mm (3 to 24 inches)
Weight	Top form: 55 to 150 g/m <sup>2</sup> Attached sheet: 45 to 75 g/m <sup>2</sup>
Copies	1 + 7
Max Thickness	0.635 mm (0.025 inches)

## MEDIA HANDLING

9050-9065	Front tractor push 4 pin Additional front tractor push 4 pin
9300-9300lpds	Front tractor push 6 pin with jam sensor
10300	Additional tractor push 6 pin with jam sensor

## LINE LENGTH (NUMBER OF CHARACTERS)

10 cpi	136	17.1 cpi	233
12 cpi	163	20 cpi	272
15 cpi	204	24 cpi	326

## HORIZONTAL SPACING

9050-9065-9080-10300	10, 12, 15, 17.1, 20, 24 cpi & proportional
9300-9300lpds	10, 12, 15, 17.1, 20 cpi & proportional

## VERTICAL SPACING

9050-9065-9080-10300	6, 8, 12 lines per inch 3, 4, 6, 8, 12 lines per 30 mm n/72, /144, /216, /360 per inch
9300-9300lpds	6, 8, 12 lines per inch 3, 4, 6, 8, 12 lines per 30 mm n/72, n/144, n/216 per inch

## GRAPHICS RESOLUTION (dpi)

9050-9065-9080-10300	<b>Horizontal:</b> 60, 80, 90, 120, 240, 360 <b>Vertical:</b> 60, 72, 180, 360
9300-9300lpds	<b>Horizontal:</b> 60, 72, 80, 90, 120, 144, 240 <b>Vertical:</b> 72, 144

## MEMORY

Input Buffer	128 Kb
--------------	--------

## CONNECTIVITY

9050-9065-9080	USB 2.0, Parallel, Serial
9300-10300	RS232, Ethernet 10/100
9300lpds	USB 2.0, Parallel, Serial RS232 Ethernet 10/100 lpds

## RIBBON LIFE (@ Draft)

9050-9065	15 Million Character Yield - Black
9080-9300-9300lpds-10300	25 Million Character Yield - Black

## PRINTHEAD LIFE

9050	500 Million Character Yield
9065-9080-9300	800 Million Character Yield
9300lpds-10300	

## WORKLOAD

Pages Per Month (max. 4Hrs/day)	
9050	40.000
9065	50.000
9080	57.000
9300-9300lpds	75.000
10300	75.000

## SPECIAL FUNCTIONS

Automatic paper path switching via panel or Software commands.  
Automatic gap adjustment thickness of print head based on paper thickness.  
Automatic fanfold position (zero tear-off).  
Automatic paper parking of continuous forms.

## OPERATING ENVIRONMENT

Operating Temp	10°-40.6°C (50°-105°F)
Operating Hum.	10%-90% Relative Humidity
Storage Temp.	-35°-65°C (-31°-149°F)
Storage Hum.	5%-95% Relative Humidity
Noise	54 dBA <54 dbA (10300)

## PHYSICAL DIMENSIONS

9050-9065-9080	670 x 450 x 320 mm, 21 Kg
9300-9300lpds	26.4 x 17.7 x 12.6", 46.3 lbs
10300	721 x 399 x 351 mm, 33 Kg 28.4 x 15.7 x 13.8", 72.6 lbs

## POWER REQUIREMENT

100 - 240V, Auto Range, (60 Hz - 50 Hz)
---

## POWER CONSUMPTION

9050-9065-9080	116W printing, 22W standby
9080	120W printing, 30W standby
9300-9300lpds-10300	160W printing, 30W standby

## EMULATION TYPES

9050-9065-9080 10300	Epson @ ESC/P LQ Series, IBM @ Proprinter XL24, IBM @ Personal Printer 2391 ANSI 3.64, Compuprint native commands
9300	Epson @ FX Series, IBM @ Proprinter III XL, IBM @ Personal Printer 2381 ANSI 3.64,
9300lpds	IBM 4224, IBM 4230 and Compuprint native commands

## FONTS AND BARCODES

Resident Font (all models)	Draft, Courier, Gothic, OCR-A, OCR-B
9050-9065-9080-10300 only	Prestige, Script, Presentor
9300-9300lpds only	DP Text
Barcodes (all models)	UPC-A, UPC-E, EAN-8, EAN-13, UPC/EAN ADD-ON 2, Postnet, UPC/EAN ADD-ON 5, Code39, Code128, Code11, Code93, MSI, Codabar, Code 2of5 Bidirectional/interleaved/Industrial/ Matrix, Code GP, Code BCD, C25-3BAR, Intelligent Mail BCode

## CHARACTER SETS

### Standard PC/IBM:

CS1, CS2 ; 13 EPSON and 23 ANSI national variations

### IBM, EPSON, ANSI:

CP 437 (USA), CP437G (Greek), CP437SL (Slavic), CP850 (Multilingual), CP851 (Greek), CP852 (Eastern Europe), CP853 (Turkish), CP855 (Cyrillic), CP857 (Turkish), CP858 (Euro PC Multilingual), CP860 (Portugal), CP862 (Hebrew), CP863 (French-Canadian), CP864 (Arabic), CP865 (Danish-Norwegian), CP866 (Russian), CP867 (Turkish2), CP876 (OCR-A), CP877 (OCR-B), CP1098 (Farsi), CP1250 (Latin2 Windows), CP1251 (Cyrillic Windows), CP1252 (Latin1 Windows), CP1253 (Greek Windows), CP1254 (Turkish Windows), CP1255 (Hebrew Windows), CP1256 (Arabic Windows), CP1257 (Baltic Windows), 96Greek, GOST, ROMAN-8, TASS, MAZOWIA, KOI8-U, UKRANIAN, Farsi 1, Farsi 2, KAMENICKY, CWI, IN2, BULGAR

### ISO:

8859/1 (Latin1), 8859/2 (Latin2), 8859/3 (Latin3), 8859/4 (Latin4), 8859/5 (Latin/Cyrillic), 8859/6 (Latin/Arabic), 8859/7 (Latin/Greek), 8859/8 (Latin/Hebrew), 8859/9 (Latin5), 8859/15 (Latin9)

## DRIVERS AND SOFTWARE

Drivers	Win10 (32/64), Win8 (32/64), Win7 (32/64), WinNT, 98_ME, 2000-WinXP, Win2003 (32/64), WinServer2008 (32/64), Vista NetViewMaster for Remote Printer Management
Software	

## RELIABILITY

MTBF: 20.000 hours

## Ordering Information

### Printers and Supplies

Compuprint 9050 <i>plus</i>	PRTN950P
Compuprint 9065 <i>plus</i>	PRTN965P
Compuprint 9080 <i>plus</i>	PRTN980P
Compuprint 9300 <i>plus</i>	PRTN9300P
Compuprint 9300lpds <i>plus</i>	PRTN9300IP
Compuprint 10300 <i>plus</i>	PRTN103P
Black Ribbon 15MC	PRKN407-1
Black Ribbon 25 MC	PRKN102-1

### Options

Additional Tractor 4P (9050-9065)	PRFN2TR4
Additional Tractor 6P (9080-9300-10300)	PRFN2TR6
Open Pedestal (9050-9065-9080-9300)	PRFN-PD1
Printer Stand (10300)	PRFN-PD2



**Compuprint Sales Contact**  
Italy: +39 011 9892141-133  
email: [sales@compuprint.com](mailto:sales@compuprint.com)  
website: [www.compuprint.com](http://www.compuprint.com)



**Compuprint**  
Printing and Scanning Solutions