

# Compuprint 9078 plus - 9078D plus

## Dot Matrix Printers fast and reliable for professional applications



### Reliability and robustness

New architectural solutions and innovative technologies provide the functions requested by the most modern and sophisticated application environments, as well as the highest level of reliability and ease of use. The straight paper path assures the safe handling of any types of document (single sheet, rigid forms, multicopies, labels, etc.). In addition, the front loading mechanism makes the paper feeding by the operator very easy.

### Outstanding performance with high compatibility

The 24 pin technology guarantees the best printing quality perfectly readable up to 1+7 copies. The target of these models are professional applications requiring also the printing of macro-characters, bar codes and a wide selection of character set with the EURO symbol support. The resident emulation IBM © and Epson © ensure total compatibility with the most advanced software environments. Standard configuration includes parallel and serial interfaces and the automatic switching capability.

Compuprint 9078 plus and 9078D plus represent the ideal solution for high volume of professional printing (all industrial and administrative environments) where the maximum in terms of speed, reliability and graphic resolution is requested. Compuprint 9078/9078D plus provide excellent performance in terms of printing speed (700 cps in draft @ 10 cpi up to a maximum value of 750 cps @ 15 cpi).

# Compuprint

FINMEK GROUP

# Compuprint 9078 plus - 9078D plus

## Dot Matrix Printers fast and reliable for professional applications

### Technical Specifications

Printing Technology	24 pin impact dot matrix printer
Printing Speed	<b>Draft:</b> 750 cps @ 15 cpi, 840 cps @ 12 cpi, 700 cps @ 10 cpi <b>NLQ:</b> 266 up to 400 cps @ 10 cpi (*) <b>LQ:</b> 133 up to 200 cps @ 10 cpi (*) (*) depending on font type
Line Length	136 columns @ 10 cpi
Throughput (ISO/IEC 10561)	540 pph
Paper Handling	Front single sheet + front push tractors (9078plus) Dual front push tractors for continuous form with paper sensor (9078D plus) Rear pull tractor (option) (Width from 76 to 432 mm - maximum thickness 0.64 mm) Automatic sheet feeder up to 3 bins (option) (120 sheet capable @ 80 gr/m - width from 89 to 305 mm - 1+2 copies)
Copies	1+7
Special Functions	Automatic paper path alternance Automatic Gap Adjustment (AGA) of print head based on paper thickness Zero tear-off Automatic paper parking of continuous form
Graphic Resolution (dpi)	Horizontal: 60, 80, 90, 120, 180, 240, 360 Vertical: 60, 72, 180
Vertical Spacing	6 - 8 - 12 lines per inch 3 - 4 - 6 - 8 - 12 lines per 30 mm n/72, n/144, n/216 per inch
Horizontal Spacing	10, 12, 15, 17.1, 20, 24 cpi and proportional
Barcodes	UPC/A, UPC/E, EAN8, EAN13 - UPCA/EAN ADD ON 2, UPC/EAN ADDON 5 - Code 39 - Code 128 - Code 11- Code 93 - MSI - Postnet - Codabar - 2/5 Interleaved -2/5 Matrix - 2/5 Industrial - Code GP - C25-3BAR - Code BCD - 2/5 Bidirectional
Character Set	PC standard set (CS1-CS2) - 13 National Epson set - CP 437 (USA) - MAZOWIA - CP1250 (Central Europe) - CP1251 (Cyrillic) - CP1252 (Windows Latin 1 Ansi) - 96 Greek - CP437G (Greek) - CP850 (Multilingual) - CP851 (Greek) - CP852 (Latin2) - CP853 (Turkish) - CP855 (Russian) - CP857 (Turkish) - CP860 (Portuguese) - CP862 (Hebrew) - CP863 (French-Canadian) - CP864 (Arabic) - CP865 (Norway) - CP866 (Cryllic) - CP867 (Turkish) - CP876 (OCRA) - CP877 (OCRB) - Gost - Tass - CP858 (EURO) - ISO 8859/1/2/3/4/5/6/7/8/9/15 (EURO)
Resident Fonts	Draft, Courier, Gothic, OCR-A, OCR-B, Script
Resident Emulations	Epson ® LQ 1050-2550 IBM ® Proprinter XL24E-XL24AGM (ESC/P) IBM ® Personal Printer 2391+
Interfaces	Centronics, Parallel IEEE 1284 bidirectional Serial RS232-C, RS 422-A Input buffer up to 64 Kbytes Plug-in & Play (Windows 9X environment) Automatic interface switching
Reliability	MTBF: 10.000 hours
Print Head Life	700 million characters
Ribbon Life	Black ribbon cartridge: 15 million characters
Noise Level	54 dBA
Power Supply	Tension: 120V - 220/240V Frequency: 60 Hz - 50 Hz
Physical Dimensions	670 (W) x 315 (H) x 390 (D) mm
Weight	18 Kg
Options	Automatic sheet feeder (up to three bins) Printer pedestal Rear pull tractor Colour kit for: colour ribbon (2 ML characters for each colour) "Long Life" black ribbon (up to 20 ML characters)

SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE  
All trademarks are registered by their respective companies.



# Compuprint

FINMEK GROUP

Compuprint SpA  
Via Martiri d'Italia, 26  
10014 Caluso (TO) Italy  
Tel. +39 011 98 92 111  
Fax +39 011 98 92 748  
www.compuprint.net