

Compuprint 3046/N 3056/N

The Compuprint 3046 and 3056 are designed to be the ideal solution for administrative applications as well for industrial and logistics environments.

These printers satisfy a wide range of printing solutions thanks to the architectural simplicity of the front form feed and refined printing technology. Compuprint printers are Compuprint 3046 and 3056 are suited for printing applications using multipart forms, single sheets, labels and envelopes.



Value and Features

- 24 pins print-head technology
- 450 cps (3046) and 540 cps (3056) max speed
- Complete and flexible paper path
- Single sheet and fanfold handling
- 1+4 copies capability
- Wide range of connectivity
- Easy to use
- Wide range of barcodes and fonts

Matching your needs and getting your job done in time

Compuprint 3046 and 3056 are ideal for use in a broad range of industries, from data processing, banking, pharmaceuticals or healthcare, warehouse and logistic, education and public administrations.

These printers in single or multiuser environments print at speeds of up to 400 and 500 characters per second in draft mode offering an excellent print quality with clear, crisp output of text and graphics.

Safe and simple paper management

Thanks to the possibility to choose either front or rear paper feed these printers are the best solution for all types of working environment. Straight feeding enables a wide variety of both single sheet, continuous and multiple copy forms to be managed in a safe and reliable manner.

It is also possible to install both printers a second tractor to improve the productivity.

For a broad range of connectivity

Compuprint 3046 and 3056 are available in two different configurations, Parallel/Serial/USB or Parallel/USB/LAN to let the user able the installation on networked environment. The LAN models are provided with a Network Interface Manager which is a software used to manage on-line network dot matrix printers.

Printing Technology	24 pin - serial dot matrix printers																								
Printing speed	<table border="1"> <thead> <tr> <th colspan="2">Compuprint 3046</th> <th colspan="2">Compuprint 3056</th> </tr> <tr> <th></th> <th>12 cpi</th> <th>10 cpi</th> <th>10 cpi</th> </tr> </thead> <tbody> <tr> <td>HSD</td> <td></td> <td>400 cps</td> <td>500 cps</td> </tr> <tr> <td>Draft</td> <td>360 cps</td> <td>300 cps</td> <td>360 cps</td> </tr> <tr> <td>NLQ</td> <td>240 cps</td> <td>200 cps</td> <td>240 cps</td> </tr> <tr> <td>LQ</td> <td>120 cps</td> <td>100 cps</td> <td>120 cps</td> </tr> </tbody> </table>	Compuprint 3046		Compuprint 3056			12 cpi	10 cpi	10 cpi	HSD		400 cps	500 cps	Draft	360 cps	300 cps	360 cps	NLQ	240 cps	200 cps	240 cps	LQ	120 cps	100 cps	120 cps
Compuprint 3046		Compuprint 3056																							
	12 cpi	10 cpi	10 cpi																						
HSD		400 cps	500 cps																						
Draft	360 cps	300 cps	360 cps																						
NLQ	240 cps	200 cps	240 cps																						
LQ	120 cps	100 cps	120 cps																						
Line Length	136 columns @ 10 cpi																								
Paper handling	Cut sheet: width from 102 to 420 mm / A5, A4, A3 (H/V) - length up to 364 mm Continuous form: width from 102 to 406 mm - length unlimited Paper thickness: 0,065 to 0.52 mm																								
Paper type	Cut sheet, Continuous paper, Multi-part forms, Envelopes, postcard, adhesive labels																								
Paper path	Friction feed: rear in top out, front in top out - Tractor feed: rear in top out, front in top out, bottom in top out																								
Copies	1 + 4																								
Special functions	Automatic paper parking, Zero tear-off																								
Barcodes	UPC/A - EAN8 - EAN13 - UPCA/E - Code 39 - Code 128 - 2/5 Interleaved - Postnet																								
Character set	ASCII, Italic, CP437, CP850, CP860, CP863, CP865, CP858 International Character Set: USA, France, Germany, England, Denmark, Sweden, Italy, Spain, Japan, Norway, Denmark 2, Spain 2, Latin America, Korea, Legal																								
Resident font	Draft, Courier, Roman, Sans Serif, Prestige, Script, Orator, Orator-S, OCR-A, OCR-B																								
Resident Emulations	Epson ® LQ-ESC/P																								
Interfaces	Centronics, Parallel IEEE 1284 bidirectional - Serial RS232 - USB (Base models) Centronics, Parallel IEEE 1284 bidirectional - USB - Ethernet LAN 10/100 BaseT (N models) Input buffer up to 128 Kbytes; Automatic interface switching; Plug-in & Play (Windows environment)																								
Drivers	Windows 95/98/2000/XP/Vista - Unix - Linux																								
SW Tool	Network Interface Manager - Internal web page (3046N - 3056N only)																								
Reliability	MTBF: 20.000 hours (3056/N) - 10.000 hours (3046/N)																								
Print Head Life	300 million strokes/wire																								
Ribbon life	6 million characters																								
Noise Level	<56 dBA																								
Power Supply	Tension: 100/240V; Frequency: 50-60Hz																								
Power consumption	75 W Max. (printing), 15 W (standby)																								
Physical Dimensions & Weight	623 (W) x 395 (D) x 173 (H) mm - 13 Kg (3056/N) - 623 (W) x 365 (D) x 173 (H) mm - 13 Kg (3046/N)																								


SFERAL WWT - Compuprint SALES CONTACTS

Italy: (+39) 011 9892 141 -
 Other Countries: (+39) 011 9892 141 -
 Email: sales@sferalwwt.com -
 Website: www.sferalwwt.com -


Ordering Information
Printers and Supplies

Compuprint 3046 Basic Printer (P-S-U)	PRTN3046
Compuprint 3046 LAN Printer (P-U-N)	PRTN3046N
Compuprint 3056 Basic Printer (P-S-U)	PRTN3056
Compuprint 3056 LAN Printer (P-U-N)	PRTN3056N
Compuprint Black Ribbon Cartridges(8 pcs)	PRK3050-8

Options

Optional second tractor (3046-3056)	PRFN3056
-------------------------------------	----------

The information contained in this document is subject to change without notice. All company and product names mentioned herein are trademarks or registered trademarks of their respective owners.
 Copyright © 2009 Sferal wwt