

# Compuprint

● ● ● ● Printing and Scanning Solutions

The economic and most versatile

## Multifunctional Flatbed Printer

for DIY warehouses and logistic departments



- ✓ onboard network connection
- ✓ bright display for clear information
- ✓ fanfold paper feed from the rear
- ✓ front load for single sheets
- ✓ handles up to 6 copies

## Compuprint **SP40** *plus* Tractor



**Sustainable by low energy consumption  
and longlasting consumables**

# Compuprint



Printing and Scanning Solutions

## Compuprint SP40 *plus* Tractor – The multifunctional flatbed printer

### Technical Data

Print Technology	Impact - Serial dot matrix printer
Print Speed	HSD: 580 cps DRAFT: 400 cps, NLQ: 200 cps, LQ: 133 cps (@ character density of 10 characters/inch)
Print Width	65 - 244 mm, max. 94 chars @10cpi, 112 chars @12cpi, 141 chars @15cpi
Paper types	Single sheets (length: 65 - 470 mm), envelopes, labels, passbooks (horizontal & vertical) Fanfold & multi copy sheets: 40gr/m <sup>2</sup> bis 200gr/m <sup>2</sup> – thickness: 0,65 mm to 2,7 mm (continous paper only PRT0626-T)
Copies	1 original sheet + 6 Copies
Features	+ automatic paper alignment, automatic paper margin detection + optical recognition of markers, horizontal and vertical folded passbooks printable + configuration can be done either by scannable configuration sheets, by PC-software or by webbrowser
Display	LCD-Display, 2 lines with 16 digits each, different languages selectable
Resolution	360 dpi x 360 dpi (dpi : dots per inch)
Character Sets	21 internat. char. tables, 28 internat. character sets inclding Gost, Mazovia, Farsi
Barcodes	UPC A/E, EAN 8/13, Code 11/39/93/128, ADD-ON 2/5, BCD, MSI, 2/5Interleaved, 2/5 Matrix, 2/5 Industrial, Postnet, Codabar
Fonts	Draft, Courier, Gothic, Prestige, Presentor, Script, OCR-A/B, Boldface
Standard emulations	EPSON LQ2550/1170 (LQ 570), Olivetti PR2/PR40plus/PR2845, Wincor HPR 4915 IBM: Personal Printer 2390+, Proprinter XL24 (AGM), 4722, 9068, Unisys EFP
Interfaces	Ethernet 10/100 Base-T, USB 2.0, parallel, serial (RS-232) automatic interface detection
Input Buffer	max 256 Kbytes
Drivers	Windows 10 - 7 (32 & 64 bit) incl. Server 2012/08/03 – signed; Linux (Ubuntu)
Reliability	MTBF (error-free printing) > 10.000 hours
Printhead	24 pins – Durability: 400 million characters (Draft) (= > 1 bn strokes / wire)
Ribbonlife	Standard: up to 10 million characters (Draft) – Eco version: up to 4 M chars (Draft)
Noiselevel	< 54 dB (A)
Power Supply	Universal power supply: 100-230V, 60-50Hz
Power Consumption	on printing: 45 W; Standby: 3 W; switched off: 0 W
Dimensions & Weight	396 (W) x 200 (H) x 295 (D) mm – 8 kg (without tractor unit)
User Manual	PDF-file, English only



### Printer Models

Compuprint SP40plus with tractor for fanfold paper	PRT0626-T
Compuprint SP40plus - parallel/serial/LAN	PRT0626-LAN
Compuprint SP40plus - parallel/serial/USB	PRT0626
Compuprint SP40plus - parallel/2x serial	PRT0628
Compuprint SP40plus with MSCR & MICR	PRT0630
Compuprint SP40plus with A4-Color-Scanner	PRT0631
Compuprint SP40plus with MSCR, MICR & Scanner	PRT0632

### Ribbons

6 Ribbons, black, 10 Mio. Char. (Draft)	PRKN6287-6
6 Ribbons, black, 4 Mio. Char. (Draft)	PRKN6240-6



### Compuprint

Edisonstr. 13  
63512 Hainburg  
GERMANY  
Tel. +49 6182 9272-233  
[info@compuprint.de](mailto:info@compuprint.de)  
[www.compuprint.de](http://www.compuprint.de)

Via Cottolengo 77  
10079 Mappano (To)  
ITALY  
International:+39 011-9892-133  
[sales@compuprint.com](mailto:sales@compuprint.com)  
[www.compuprint.com](http://www.compuprint.com)